

## CLAIM AMENDMENTS

### IN THE CLAIMS

This listing of the claims will replace all prior versions, and listing, of claims in the application or previous response to office action:

1. (Currently Amended) A computer system comprising:  
at least two ~~one-server modules~~module;  
a midplane associated with the at least two server modules, the midplane operable to receive the at least two server ~~modules~~module and to provide a unique address for each server module based on the location of each ~~the-server module~~ modules on the midplane;  
at least one address module associated with the at least two server modules, the address module operable to obtain the unique address from the midplane for each server module and to calculate a start-up time for each server module based on the unique address for each server module; and  
at least one power supply associated with the midplane, the power supply operable to sequence power to the server modules based on the start-up times for each of the server modules.
2. (Currently Amended) The system of Claim 1 wherein the server modules ~~comprise module~~ ~~comprises a blade~~ servers~~server~~.
3. (Currently Amended) The system of Claim 1 wherein the server modules ~~comprise module~~ ~~comprises a brick~~ servers~~server~~.
4. (Currently Amended) The system of Claim 1 wherein the midplane comprises a circuit board including two ~~one~~ or more connectors coupled to the midplane and two~~one~~ or more resistors coupled to the midplane.

5. (Original) The system of Claim 4 wherein the connectors are operable to provide an interface between the server modules and the midplane.

6. (Original) The system of Claim 4 wherein each connector is operable to interface with one server module.

7. (Original) The system of Claim 4 wherein the midplane provides a unique address to each server module through resistor strapping the one or more resistors.

8. (Original) The system of Claim 1 wherein the midplane is further operable to provide an interface between the server modules and the power supply.

9. (Original) The system of Claim 1 wherein the power supply is operable to provide power to each server module upon expiration of the start-up time for each server module.

10. (Currently Amended) The system of ~~claim~~ Claim 1 further comprising a management controller associated with the midplane, the management controller operable to provide sequence redundancy by sequencing power to the server modules if the midplane experiences a failure.

11. (Original) The system of Claim 1 wherein each address module includes a timer, the address module further operable to set the timer with the start-up time and the timer operable to count down from the start-up time.

12. (Currently Amended) The system of Claim 1 further comprising a switch ~~one or more switches~~ associated with each ~~the server module modules~~ and the at least one ~~address module modules~~, each switch ~~the switches~~ operable to accept a command from the address modules to switch between an on position and an off position.

13. (Currently Amended) The system of Claim 12 where at the expiration of the start-up time the address module switches ~~a selected~~the switch to the on position allowing an associated server module to receive power from the power supply.

14. (Currently Amended) A method for autonomous power sequencing in a computer system, the method comprising:

receiving ~~two or~~one or more server modules;

providing a unique address for each server module based on the location of ~~each~~the server ~~module~~modules on a midplane;

obtaining the unique address for each server module from the midplane;

calculating a start-up time for each server module based on the unique addresses of the server modules; and

automatically sequencing power to the server modules based on the start-up times for the server modules.

15. (Currently Amended) The method of Claim 14 wherein the server modules ~~comprise module comprises a blade~~ serversserver.

16. (Currently Amended) The method of Claim 14 wherein the server modules ~~comprise module comprises a brick~~ serversserver.

17. (Original) The method of Claim 14 wherein calculating the start-up time comprises:

obtaining a multiplication factor for the server modules; and

calculating the start-up time using the multiplication factor.

18. (Original) The method of Claim 14 further comprising:  
setting a timer with the start-up time;  
counting down on the timer until the start-up time expires; and  
on the expiration of the start-up time, switching a switch to an on position that allows the server module to receive power from a power supply.

19. (Currently Amended) The method of Claim 14 wherein receiving the server modules comprises inserting each the server module ~~modules~~ into at least one ~~connector~~ coupled to the midplane.

20. (Original) The method of Claim 14 wherein providing a unique address for each server module comprises strapping one or more resistors to the midplane whereby each connector provides a unique address for the server module associated with the connector.

21. (Original) The method of Claim 14 wherein automatically sequencing power to the server modules comprises providing power to the server modules one server module at a time.

22. (Original) The method of Claim 14 wherein automatically sequencing power to the server modules comprises providing power to each server module upon the expiration of the start-up time for each server module.

23. (Currently Amended) A computer system comprising:

two ~~one~~ or more server modules operable to process data;

one or more midplanes associated with the server modules, the midplanes including a plurality of connectors, each connector operable to interface with one server module and provide a unique address for each server module based on which connectors the server modules interface with;

one or more address modules associated with the server modules, the address modules operable to obtain the unique address from the connectors for each server module and to calculate a start-up time for each server module based on the unique address for each server module;

one or more power supplies associated with the midplanes, the power supplies operable to provide power to the server modules in a sequence determined by the start-up times for the server modules; and

one or more chassis operable to house the server modules, the midplane, and the power supply.

24. (Currently Amended) The system of Claim 23 further comprising one or more management controllers associated with the midplanes, the management controllers operable to provide sequence redundancy when one or more of the midplanes experiences a failure.

25. (Original) The system of Claim 23 further comprising one or more cabinets housing one or more of the chassis.